

ပ



(19)

JAPANESE PATENT OFFICE

PATENT ABSTRACTS OF JAPAN

(11) Publication number:

(43) Date of publication of application: 29.03.1994

06090409 A

H04N 5/44 (51) Int. CI H04N 5,60

(21) Application number:

08.09.1992 04266635 (22) Date of filing: (54) TELEVISION RECEPTION CIRCUIT


PURPOSE: To provide the television reception circuit which outputs a sound signal after such correction that the high frequency component of the sound signal is reduced in the case of the weak electric field reception (57) Abstract:

CONSTITUTION: In a range correction block 18, a sistor TR Q3 when judging it by detection information inputted to a detection information input terminal that the PLL lock state is not released, and the block 21 out-When the 'Low' signal is outputted, a TR Q1 is turned on by an input sound signal, and the sound signal is outputted from a sound output terminal through the tone control block 21 outputs a 'Low' signal to a tranputs a 'Hi' signal to the TR Q3 when judging it by deemitter electrode of the TR Q1 and an output resistection information that the PLL lock state is released.

(71) Applicant: CASIO COMPUT CO LTD

SUMI HIDETOSHI (72) Inventor: sound signal, and the sound signal is outputted to a sound amplifier through the sound output terminal

COPYRIGHT: (C)1994, JPO&Japio



BEST AVAILABLE COPY file:///C//Documents%20and%20Settings/deeptid/Desktop/DEEPTI---20050817--20/dwl/JP06090409A2.htm (1 of 2) [8/18/2005 5:22:05 PM]

JP06090409A2.tif Page 1

tance HO; and when the "Hi' signal is outputted, the TR C3 is turned on, and the signal pass band characteristic is changed by the connection capacity in the TR Q3 to reduce the high frequency component of the

10C CY

file:///C|/Documents%20and%20Settings/deeptid/Desktop/DEEPTI---20050817--20/dw//JP06090409A2.htm (2 of 2) [8/18/2005 5:22:05 PM]

BEST AVAILABLE COPY